

General information

Battery name	12MFB120T
Product Range	VLA Tubular Positive Plates
Polarity	DX
Technology	Flooded
Application	Light Motive Power / Leasuring
Standard ref.	EN 60254-1



The new FORCEblock range has been designed to be a complete and reliable solution for ALL those LIGHT MOTIVE POWER applications such as EV, cleaning machines, small pallet trucks, aerial platform and lifts, as well as wheelchairs and golf cart. Now available in vented and sealed version, both flat and tubular plates models can be defined to properly satisfy the specific application.

General characteristics

Voltage (V)	12
Capacity 5h	120
Capacity 20h (Ah)	150
Cold cranking Amps (CCA), EN (A)	
Energy at 20hrs rate and 25C (Wh)	1790
Cranking Power 10" at -18°C (KW)	

Dimensional group	DIN Compact 120
Sizes (LxWxH) (mm)	345 x 170 x 290
Base Hold-Down	B0
Lay-out/Terminals	0 / DIN
Battery weight \pm 5% (kg)	36.5

Box

Case	PP/PE
Lid	PP/PE
Plug	PP/PE

Colour	Nat. Opaque
Colour	Black
Colour	Black

Drawings

Lay-out	Base hold down	Terminals type
---------	----------------	----------------

12MFB120T

