

TECHNICAL DATA SHEET

9.550.2

Applications



CYCLIC



SOLAR



MARINE

PHYSICAL CHARACTERISTICS

	SI Units	US Units
Length	242 mm	9.5 inch
Width	175 mm	6.9 inch
Height	190 mm	7.5 inch
Typical weight	16 kg	35.3 lbs

Specifications :

- Nominal voltage: 12 V
- Rated capacity: 60 Ah (at C_{20} and 30 °C)
- Plate technology: Calcium / Calcium
- Separator: Polyethylene + glass mat
- Electrolyte: Sulphuric acid; analytical grade
- Standards: IEC 60254; IEC 61427
- Case / Lid material: Polypropylene
- Lid type: Kamina
- Terminal type: Top / Automotive
- Carrying Handles: Available
- Cycles at 50% DoD: up to 400 cycles
- PVES applications: up to 800 cycles

Performance characteristics:


BATTERY DISCHARGE PERFORMANCE AT 25°C

Discharge rate		C ₅ (5 h)	C ₂₀ (20 h)	C ₁₀₀ (100 h)	Capacity at 25 A		
End of discharge voltage		10.20 V	10.50 V	10.80 V	10.50 V		
Discharge capacity		50 Ah	60 Ah	70 Ah	100 min		
Temperature correction factor of discharge C ₅ (5 h) capacity							
Temperature	-10 °C	0 °C	20 °C	25 °C	30 °C	35 °C	40 °C
Correction factor	0.76	0.82	0.94	0.97	1.00	1.03	1.06


BATTERY CHARGE CONDITIONS (according DIN 41773 and DIN 41774)

Charging profiles: WaW0 and IUla Charge factor: 1.10 – 1.20


WaW0 – (double slope taper) characteristics for flooded batteries)




Charging times with WaW0-characteristics in hours for PzS batteries at 30 °C



IUla –characteristics for flooded batteries



Charging times with IUla-characteristics in hours for PzS batteries at 30 °C



It is mandatory to check the electrolyte level every 3 months and top up with deionized water to the markings.