

TECHNICAL DATA SHEET

9.605.1 MF

Applications



CYCLIC



SOLAR



MARINE

Electrical specification

Voltage:	12V
Capacity C ²⁰ :	140 Ah
Cold cranking current:	850 A [EN]
Cold cranking current:	500 A [DIN]

Mechanical specification

Dimensional group:	A
ETN reference:	640 020 085
DIN reference:	64020
Dimensions ^A in mm (LxWxH):	513x189x220
Cell Layout:	3
Terminal Type:	1

Container

Case	Material	Polypropylene
	Bottom hold-down	B0
	Colour	Black

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Black

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Black

Handles	Material	Polypropylene
	Position	Sides - on container
	Colour	Black


Battery classification as per EN 50342 - 6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V2	E2

Weight^B

Battery weight in kg:	22.60
Acid weight in kg:	11.90
Total battery weight in kg:	34.50

Layout



Hold - down



Separator

Type	PE with Glass Mat
------	-------------------

A. Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.

B. Weight may vary $\pm 5\%$.